

JB1113N Liquid Dispenser




JB1113N with Foot Pedal and [30cc Syringe](#)

A popular analog dispenser series featuring dual 110/220V operation. An all-purpose dispenser, versatile and easy to use in a few simple steps – hook up the barrel adapter assembly (selection included) - connect the air and power - set the timer - load the barrel with material - set the air regulator – press the foot switch and start dispensing.

Suitable for all types of fluids, includes a suck-back feature to ensure low viscosity liquids do not drip. Timing interval from 0.01 to 31 seconds.

Features

- Dispense Timer
- Wide range of applications
- Barrel suck-back ensures no dripping
- low-cost system with high reliability



Front Panel of the JB1113N

Models

[JB1113N](#)

[Dispenser 110/220V CE](#)

Specifications

Size:	8.63" x 8.50" x 2.63" (21.92 x 21.59 x 6.68cm)
Dispense time:	0.01 - 31 seconds
Cycle:	Momentary with time or continuously maintained
Voltage:	100 - 240 VAC 50/60Hz
Internal Voltage:	24 VDC
Air input:	70 to 100 psi (5 to 7 bar)
Air output:	1-100 psi (0.1-7 bar)
Standards:	CE approved, RoHS Compliant
Weight:	3.5 lbs (1.59 kg)

Kontakt, Interflux Danmarks ApS på 75 38 39 22 eller interflux@interflux.dk