



Technical information

MultiEx N7-TS[®]

ReadyMix



Technical Data

Density at 20°C	0,978 g/m³
Viscosity at 20°C	6,8 mPas
ph-value at 20°C	6,9
Boiling temperature	> 100°C
Explosion risk	none
Application temperature	19 - 30°C
Application	pure
Storing frost-free	in original container
Waste key	070104
WPC	1
Hazards classification	no marking required
VOC-content	< 20%*

Water based pH-neutral broadband cleaning and / or rinsing detergent.

Cleans SMD-paste, dust, fats, oils, colophonium and flux (to be verified) quickly, thoroughly and with best material protection e.g. from stencils, misprints, aluminium, stainless steel, etc.

ReadyMix for direct use in the cleaning system

This single-phase TS-cleaner reaches its best efficiency at 20 - 25°C.

*This product is VOC reduced < 20 % and as such it is not subject to the consumption limitation of the EU directive 1999/13/EG (in Germany 31. BImSchV)

Applications

Cleaning of:	
SMD adhesive	+*
Solder paste	++*
Low voc flux	++*
Colophonium flux	+*
Waterbased flux	++*
Solder paste (soldered)	++*
Oil/Grease	+*

Please be aware: The product may irritate mucuous membrane, skin and eyes!

For commercial use only!

Your MultiEx N7-TS supplier:

Process

			PS-PowerSpray Systems
			AF-AirFlow Systems
			FC-Stencil under-/flipside

Part No. 090640-RM25-2 // Contents: 25 l

Part No. 090640-RM1-2 // 1.000ml-bottle/PU: 10 pc.

Made in Germany

Part No. 090640-RM200//200l-drum

***++ = ideal for application, + = recommended, o = usable but not recommended, - = not recommended**

Note: The spreadsheet only shows a general overview of the cleaning media specifications. Rinsing with tap water with a too high lime concentration may cause lime residues after drying. Cleaning tests are reasonable and necessary to determine the optimum cleaner configuration. Such tests may be carried out directly at the **kolb** Demonstration Center in Willich / Germany or can be initiated by contacting one of our international subsidiaries.

Kolb Cleaning Technology GmbH
 Karl-Arnold-Str. 12 · D - 47877 Willich
 Further information: www.kolb-ct.com

Phone +49 (0) 2154 9479 - 38
 Fax +49 (0) 2154 9479 - 47
 e-mail info@kolb-ct.com

All modifications due to technical improvements are subject to change without notice.